AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application.

LISTING OF CLAIMS:

 (Currently amended) A method of securing access to resources in a computing device, comprising the steps of:

storing an encrypted access code in a $\frac{1}{2}$ memory location with $\frac{1}{2}$ the computing device;

receiving a password to access the resources;

encrypting the password to produce a encrypted password; comparing the encrypted password to the encrypted access code;

allowing access to the resources if the encrypted access code matches the encrypted password.

- (Original) The method of claim 1 wherein the step of storing an encrypted access code comprises the step of storing a hashed access code.
- (Original) The method of claim 2 wherein the step of encrypting a password comprises the step of hashing a password.
- (Original) The method of claim 1 wherein the encrypted access code is stored in a memory that cannot be externally modified.

TI-34921 -5-

Application No. 10/618,861 Amendment dated December 12, 2006 Reply to Office Action of April 10, 2006

 (Original) The method of claim 1 wherein the step of allowing access comprises the step of allowing access to testing resources if the encrypted access code matches the encrypted password.

6. (Original) The method of claim 1 wherein the step of allowing access comprises the step of allowing access to change system parameters if the encrypted access code matches the encrypted password.

(Currently amended) A computing device comprising:

a processing system;

a memory coupled to the processing system for storing an encrypted access code;

input circuitry <u>coupled to the processing system</u> for receiving a password to access the resources;

wherein the processing circuitry:

encrypts the password to produce a encrypted password;

compares the encrypted password to the encrypted access code;

allows access to the resources if the encrypted access code matches the encrypted password.

 (Original) The computing device of claim 7 wherein the encrypted access code comprises a hashed access code.

(Original) The computing device of claim 8 wherein the encrypted password comprises a hashed password.

TI-34921 -6-

- 10. (Original) The computing device of claim 7 wherein the encrypted access code is stored in a memory that cannot be externally modified.
- 11. (Original) The computing device of claim 7 wherein the processing system allows access to testing resources if the encrypted access code matches the encrypted password.
- 12. (Original) The computing device of claim 7 wherein the processing system allows access to system parameters if the encrypted access code matches the encrypted password.

Please add the following new claims:

- 13. (New) The method of claim 1 wherein the memory location is within a processing system in the computing device.
- 14. (New) The method of claim 13, wherein the processing system is a baseband processing system.
- 15. (New) The method of claim 13 wherein the memory location is in a memory subsystem within the processing system.
- 16. (New) The method of claim 15 wherein the memory subsystem comprises a memory array in which after data is written to the array, further writing to the particular memory location is disabled, such that the data cannot be overwritten.

- 17. (New) The method of claim 16 further including at least one of a read only memory (ROM) coupled to the memory array and a random access memory (RAM) coupled to the memory array.
- 18. (New) The method of claim 16 wherein some portions of the memory array are externally accessible but not modifiable.
- 19. (New) The method of claim 16 wherein some portions of the memory array are not externally accessible and are not modifiable.
- (New) The method of claim 16 wherein an encryption key is stored in the memory array.
- 21. (New) The method of claim 20 wherein the encryption key is generated by a random number generator internal to the processing system.
- 22. (New) The method of claim 21 wherein the encryption key is generated at the time of production of the processing system.
- (New) The method of claim 15, further including at least one processor coupled to the memory subsystem.
- 24. (New) The method of claim 23, further including a non-volatile memory system coupled to the processing system wherein the non-volatile memory system is external to the processing system but internal to the computing device.

TI-34921 -8-

- 25. (New) The method of claim 24, further including a radio frequency (RF) system coupled to the processing system.
- 26. (New) The method of claim 16, further comprising at least one of the following stored in the array; a test ID; a manufacturer's public key; a die identification number.
- 27. (New) The method of claim 17 wherein the read only memory (ROM) further comprises at least one of the following: a program for determining whether boot system firmware is available for uploading at power-up; a program for checking authenticity and integrity of the system boot firmware; a program for preventing alternation of specific data associated with the computing device; a program for preventing alternation or swapping of firmware; cryptographic software.
- 28. (New) The method of claim 24, wherein the non-volatile memory system includes at least one of the following: firmware; application software; data files; a manufacturer's certificate; a platform certificate.
- 29. (New) The method of claim 1 wherein the encrypted password is of a different length than the received password.
- 30. (New) The computing device of claim 7 wherein the memory is a memory subsystem within the computing device.
- 31. (New) The computing device of claim 30 wherein the processing system, the memory and the input/output comprise a baseband processing system.

TI-34921 -9-

- 32. (New) The computing device of claim 31 wherein the memory location is in a memory subsystem within the baseband processing system.
- 33. (New) The computing device of claim 32 wherein the memory subsystem comprises a memory array in which after data is written to the array, further writing to the particular memory location is disabled, such that the data cannot be overwritten.
- 34. (New) The computing device of claim 33 further including at least one of a read only memory (ROM) coupled to the memory array and a random access memory (RAM) coupled to the memory array.
- 35. (New) The computing device of claim 33 wherein some portions of the memory array are externally accessible but not modifiable.
- 36. (New) The computing device of claim 33 wherein some portions of the memory array are not externally accessible and are not modifiable.
- 37. (New) The computing device of claim 33 wherein an encryption key is stored in the memory array.
- 38. (New) The computing device of claim 37 wherein the encryption key is generated by a random number generator internal to the processing system.
- 39. (New) The computing device of claim 38 wherein the encryption key is generated at the time of production of the processing system.

TI-34921 -10-

- 40. (New) The computing device of claim 33, further including at least one processor coupled to the memory subsystem.
- 41. (New) The computing device of claim 31, further including a non-volatile memory system coupled to the baseband processing system wherein the non-volatile memory system is external to the processing system but internal to the computing device.
- 42. (New) The computing device of claim 41, further including a radio frequency (RF) system coupled to the baseband processing system.
- 43. (New) The computing device of claim 34, further comprising at least one of the following stored in the array: a test ID; a manufacturer's public key; a die identification number.
- 44. (New) The computing device of claim 35 wherein the read only memory (ROM) further comprises at least one of the following: a program for determining whether boot system firmware is available for uploading at power-up; a program for checking authenticity and integrity of the system boot firmware; a program for preventing alternation of specific data associated with the computing device; a program for preventing alternation or swapping of firmware; cryptographic software.
- 45. (New) The computing device of claim 41, wherein the non-volatile memory system includes at least one of the following: firmware; application software; data files; a manufacturer's certificate; a platform certificate.
- 46. (New) The computing device of claim 7 wherein the encrypted password is of a different length than the received password.

TI-34921 -11-